

Support 4 printheads Print GS1 UDI code

- With HP TIJ 2.5 technology, taking HP original board to make sure print quality
- With a 10 inch touch screen as controller, easy to edit print message
- Support 1-4 print heads combined or separate freely
- Printing speed up to 23 pcs/s
- User-friendly interface, easy UI makes it accessible to operators of varying expertise levels
- The resolution is adjustable from 150 dpi to 600 dpi
- With RFID as encryption, more reliable for continuous sales
- Ethernet port, support communication, scale connection and scanner
- Support to print GS1, used in track and trace



Ethernet port



PARAMETERS

Technology	HP TIJ2.5			
Operation system	CE SYSTEM			
Controller	10 inch touch screen			
Print height	EPJET-1	12.7mm	EPJET-2	25.4mm
	EPJET-3	38.1mm	EPJET-4	50.8mm
Print speed	20m/min@600x300DPI 40m/min@300x300DPI 90m/min@150x300DPI			
Resolution	X:100/150/200/300/600		Y:300/600	
Print content	Text, date, counter, image, shift code, 1D&2D barcode, database, Julian date, GS1			
More functions	Authority password/date format can be set flexibly/carry bit source counter can be set/Combined barcode			
Barcode type	1D: EAN8\EAN13\EAN128\CODE25\CODE39CODE128\ UPC12\ITF-14\GS1-128 2D: PDF417QRCODE\DATAMATRIXGS1-DM\GS1-QR			
Communication	Yes, by Ethernet			
Interface	USB/Sensor/Encoder/Alarm			
Optional parts	Encoder/Alarm/4 meters cable/Adjustable brackets			
Display language	Chinese/Traditional Chinese/English/Spanish/Korean (Other can be customized)			
Printable language	Simplified Chinese/Traditional Chinese/English/Spanish/ Portugu/Indonesian/Korean/Russian/Arabic (Other can be customized)			
Font supported	Default: Arial/SourceHanSansSC Regular/ SourceHanSerifCN-Regular More: support .tff format fonts which can be imported			
Upgrade	Firmware and software both can be updated by USB			
Ink	Support both water based and solvent based ink			
Power	120W /110-220VAC/ 50/60Hz			
Environment	5℃ ~35℃ / 10%~90%			
Weight/Dimension	4.2kg/44*36*14cm			
Certification	CE			

